TECHNICAL SPECIFICATION



Replacement Jetstream® Dust & Gas Filter TH2A2P R SL

Jetstream® Dust & Gas Filter TH2A2P R SL / CBU620-000-000



DESCRIPTION

Replacement TH2A2P R SL filter for Jetstream® GVX Unit .

*Replacement Jetstream® Dust & Gas Filter TH2A2P R SL meets the requirements of EN 12941 when fitted to Jetstream® respirator.

OPTIONS

Jetstream® Dust & Gas Filter TH2A2P R SL (CBU620-000-000)

SAFETY STANDARDS

EN 12941















SPECIFICATIONS

Classification TH2A2P R SL

Usage

R (Reusable)



Activated Carbon Layer

Yes

Maximum Total Inward Leakage (TIL) 2% When Fitted To Jetstream

UK Assigned Protection Factor

20 When Fitted To JetStream GVX Unit

Filter Material

Pleated Media & Ativated Carbon

Filter Shelf Life 3 Years



Product Weight

TH2A2P R SL Filter 592g



Filter Type

Organic Vapours, Nusance Odours and Particulate



(D) Resistance to dust clogging

Yes - Mandatory Test In EN12491

Minimum Filtration Efficiency

98%

Nominal Protection Factor

50 When Fitted To JetStream GVX Unit

Metal Free

No

Filter Casing Material

ABS



BSI Kitemark

Yes

RANGE

Jetstream

ACCESSORIES

DOWNLOADS

Image Pack (ZIP)

doc-jetstream.pdf (PDF)













