



CODE: SPVG - 4131X
SIZE: 9 – 10 (L-XL)

13 - GAUGE WHITE POLYESTER LINER, RED PVC COATED GLOVES

USER INFORMATION


These products are classed as Category II Personal Protective Equipment (PPE) by the PPE REGULATION 2016/425 as brought into UK law and have been shown to comply with this Regulation through the Designated Standard(s): EN ISO 21420:2020, EN 388:2016 + A1:2018.

Please read these instructions carefully before using these gloves. The gloves are designed to minimise the risk of injury from specific hazards as identified by the marking on the product. However, always remember that no item of PPE can provide full protection and care must always be taken while carrying out the risk-related activity.

Intended use: Construction, building, and general handling against mechanical risks.

Storage and transport: When not in use, store the product in a well-ventilated area away from extremes of temperature. Glove performance quoted is based on laboratory data and may not reflect the actual duration of protection in the workplace due to other factors influencing the performance such as temperature, abrasion, degradation etc.)

Performance and limitation of use – This product has been tested in accordance with (EN388:2016 + A1:2018, EN ISO 21420:2020)


EN 388:2016+A1:2018	LEVEL	EN 388:2016+A1:2018
Abrasion resistance:	[4]	 4131X
Blade cut resistance:	[1]	
Tear resistance:	[3]	
Puncture resistance:	[1]	
TMD cut resistant	[X]	

X: means this test was not carried out.

0: indicates that the glove falls below the minimum performance level for the given individual hazard **Test results relate to the palm area of the glove*

Do not use near to moving machinery – entanglement hazard (if tear resistance level equal or greater level 1)

EN388:2016+A1:2018 Levels are based upon the table below.

	Level	1	2	3	4	5	
	Abrasion resistance (number of cycles)	100	500	2000	8000	-	
	Blade cut resistance (index)	1.2	2.5	5	10.0	20.0	
	Tear Resistance (N)	10	25	50	75	-	
	Puncture resistance (N)	20	60	100	150	-	
	Test	Level A	Level B	Level C	Level D	Level E	Level F
	Straight blade cut (TDM) resistance (N)	2	5	10	15	22	30
Impact protection		Pass (P) or fail (No marking)					

The glove does not contain any substances that are known to cause allergies.

Additional information relating to substances contained in the glove which are known to cause allergies will be supplied upon request.

Attention:

Cleaning: Wipe with wet cloth, all performance levels quoted are for products in new condition and cannot be guaranteed if the product is laundered, hence it is recommended that these products should not be washed or dry cleaned.

Donning and doffing:

1. Check whether the protective gloves are damaged before each use.
2. Please wear protective gloves before operating dangerous processes.
3. After removing contaminated gloves, avoid exposure of pollutants and contact with skin.
4. The contaminated gloves should be wrapped before being discarded.
5. Choose gloves of appropriate size.

CTC, 4, Rue Hermann Frenkel, 69367 Lyon Cedex 07, France (Notified Body 0075)

CMT Group, Riverbridge House, Anchor Boulevard, Crossway Business Park, Kent, DA2 6SL United Kingdom
Made in China

