

Latex Coated Palm Gloves


Code: **SGGT**

7-gauge polyester and fleeced liner with latex crinkle coating on palm and front of fingers gloves

- EN 388: 2016+A1: 2018
- 2242X
- EN 511: 2006
- Latex crinkle coated palm and polyester fleeced lined gloves, cold resistant with superb grip and abrasion, high dexterity, and flexibility.
- Knitted elasticated cuffs with breathable back of hand and fingers.
- Suitable for: Construction applications, Mechanical, Engineering, General handling
- Sizes: 8 - 10 (M-XL)
- Supplied in pack quantities of 12 only.
- Plastic free packaging



EN388:2016+A1:2018 Levels are based upon the table below.

	Level	1	2	3	4	5	
	Abrasion resistance (number of cycles)	100	500	2000	8000	-	
	Blade cut resistance (index)	1.2	2.5	5	10.0	20.0	
	Tear Resistance (N)	10	25	50	75	-	
	Puncture resistance (N)	20	60	100	150	-	
Test	Level A	Level B	Level C	Level D	Level E	Level F	
Straight blade cut (TDM) resistance (N)	2	5	10	15	22	30	
Impact protection	Pass (P) or fail (No marking)						

EN 388: 2016+A1: 2018



Another innovative product from

