



**gravity-s**


| HS CODE                                                                                                       |
|---------------------------------------------------------------------------------------------------------------|
| 63079098                                                                                                      |
| CARTON SIZE / PCS.                                                                                            |
| 60 x 40 x 24 / 12                                                                                             |
| AET N° 2777/10958-01/E08-01                                                                                   |
| <b>Satra Technology Europe Ltd., N° 2777,</b><br>Bracetown Business Park, Clonee,<br>Dublin, D15YN2P, Ireland |
| MODULE D FI14/14003.01                                                                                        |
| <b>SGS Fimko Oy, N°0598</b><br>Takomotie 8,<br>00380 HELSINKI, Finland                                        |

|                                                                                          |                                                                                                                                                                                  |
|------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| REF.                                                                                     | FA 30 900 20                                                                                                                                                                     |
| LG.<br> | 1.4 m / 2.0 m (connector included)<br>-----<br>Max. 140 KG                                                                                                                       |
| CE                                                                                       | EN 355:2002                                                                                                                                                                      |
| MAT.                                                                                     |  45 mm<br> PES |
|         | INTERNAL ABSORBER                                                                                                                                                                |
|         | <br>FA 50 105 22B / FA 50 218 60                                                               |
|        | YES                                                                                                                                                                              |
| +                                                                                        | PPE-R 11.063<br> X1                                                                           |
|       | 1.01 KG                                                                                                                                                                          |



**Largeur de l'absorbeur d'énergie**  
Width of the energy absorber  
**Ancho del absorbedor de energía**  
Larghezza del assorbitor di energia  
**Breite des Falldämpfers**

LG.



**Longueur Poids maxi utilisateur**  
**Length Max. user weight**  
**Longitud Peso máximo del usuario**  
**Lunghezza Peso Max. dell'utente**  
**Länge Höchstgewicht des Benutzers**



**Matière connecteur haut / connecteur bas**  
Material of top connector / bottom connector  
**Material conector alto / conector bajo**  
Materiale connettore alto / connettore basso  
**Material oberes / unteres Verbindungselement**



**Ouverture**  
Gate opening  
**Apertura**  
Apertura  
**Öffnung**



**Homologué pour le travail à proximité d'arêtes vives**  
Approved for work near sharp edges  
**Homologado para trabajo cerca de aristas vivas**  
Omologato per lavoro in prossimità di spigoli vivi  
**Zugelassen für Arbeiten in der Nähe scharfer Kanten**